

PRODUCT FEATURES

- Low profile LED task lighting solution.
- Constructed of aluminum, available in a white finish with frosted glass.
- Available in five lengths to fit a wide range of applications.
- Easy installation options with hard-wire or convenient plug-n-play design and on-off switch.
- Join units together with connector cords (sold separately).
- Protected by a 5-year warranty. Please visit the "About Us" page on techlighting.com for more warranty details.

LAMPING

With five convenient lengths, the ability to power up to 70 linked units from a power connection, a standard on/off switch, a reliable integrated driver, an optional occupancy sensor and color temperature/CRI options. Glyde LED Direct Wire is perfect for residential or commercial use.

ACCESSORIES

JUMPER CONNECTORS

Can be used to link one undercabinet housing to another or to a splice box. The maximum wattage for a single run is 600 watts. Use female to female connector to create longer lengths or contact us for custom lengths. Nominal length.

700UCJC	LENGTH*	COLOR
01	1"	B BLACK
03	3"	W WHITE
06	6"	
12	12"	
24	24"	



*FOR CUSTOM LENGTHS, CONTACT OUR FACTORY

FEMALE TO FEMALE CONNECTOR

Joins two jumper connectors together.

700UCFFC	COLOR
	B BLACK
	W WHITE



PLUG-IN WALL FEED

Can be used to plug one undercabinet housing directly into an outlet.

700UCPL	LENGTH*	COLOR
	24 24"	B BLACK
	72 72"	W WHITE



*FOR CUSTOM LENGTHS, CONTACT OUR FACTORY

ORDERING INFORMATION

700UCGLY	CRI	CCT	LENGTH	FINISH
9	90 CRI	2 2700K	7 7.5"	W WHITE
		3 3000K	12 12"	
		35 3500K	18 18"	
			24 24"	
			30 30"	

700UCGLY _____

JOB NAME _____

NOTES _____



SPLICE BOX

Required for hardwire applications. Conduit is fed into the back and Jumper Connector ports on each side can feed power to Unilume LED Slimline runs in two directions. The 1" Jumper Connector can be used to place the Splice Box next to the Undercabinet Housing. Longer Jumper Connectors can be used to place the Splice Box in a more convenient or remote location. Includes 3/8" conduit connector.



700UCSB	FINISH
	B BLACK
	W WHITE

DIMENSIONS

	7"	12"	18"	24"	30"
HEIGHT	.9"	.9"	.9"	.9"	.9"
WIDTH	5.3"	5.3"	5.3"	5.3"	5.3"
LENGTH	7.5"	11.6"	17.2"	23.2"	29.2"
NET WEIGHT	1.2	1.7	2.2	2.9	3.4

LAMPING SPECIFICATIONS

	7"	12"	18"	24"	30"
INTEGRATED LED	Yes	Yes	Yes	Yes	Yes
DELIVERED LUMENS	300	675	900	1275	1670
WATTS	6W	11.8W	15.7W	22.3W	28.3W
EFFICACY					
MAX WATTAGE	6W	11.8W	15.7W	22.3W	28.3W
INPUT VOLTAGE	120V				
DIMMING TYPE*	ELV				
CCT	2700K, 3000K or 3500K				
CRI	90				
LED LIFETIME	50,000 hours to 70%				
FIELD SERVICEABLE LED	No				
LAMP BASE	Integrated LED				
LAMP INCLUDED?	Yes				
WARRANTY**	5 year limited				

*Dimming information available at www.techlighting.com/Downloads#dimming
 **Visit techlighting.com for specific warranty limitations and details.

SPECIFICATIONS

HARDWARE MATERIAL	Aluminum
SHADE MATERIAL	Glass
DAMP LISTED	Yes
MOUNTING DETAILS	
GENERAL LISTING	ETL
INCLUDES	

T20/T24 INFORMATION

	INTEGRATED LED	REPLACEMENT LED LAMP	NO LAMP*
This product can be used to comply with California Building Energy Efficiency Standards 2016 Title 24 Part 6.	Yes		
This product meets California Appliance Efficiency Standards 2016 Title 20 and may be shipped to and sold in California.	Yes		

*If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.

