

PORT 13 ROUND WALL



The elegantly simple design of the Port outdoor wall sconce is completely backlit to create a soft glow of illumination enhancing the geometry of the fixture. The Port is available Round or Square and comes in two sizes (8", 13") to meet the architectural scale of its surroundings. Port wall sconces feature energy-efficient, fully dimmable integrated LED lighting. Available in three finishes: Black, Bronze and Charcoal.

High quality LM80-tested LEDs

for consistent long-life performance and color

Outstanding protection against the elements:

- Marine-grade powder coat finishes
- Stainless Steel mounting hardware
- Impact-resistant, UV stabilized frosted acrylic lensing
- IP-65 Rated

SPECIFICATIONS

DELIVERED LUMENS	662
WATTS	32
VOLTAGE	Universal 120-277V, with integral transient 2.5kV surge protection (driver)
DIMMING	0-10, ELV, TRIAC
LIGHT DISTRIBUTION	Symmetric
MOUNTING OPTIONS	Wall
PERFORMANCE OPTIONS	In-Line Fuse / Surge Protector
CCT	3000K
CRI	90+
COLOR BINNING	3 Step
BUG RATING	B0-U3-G1
DARK SKY	Non-compliant
WET LISTED	IP65
GENERAL LISTING	ETL
CALIFORNIA TITLE 24	Can be used to comply with CEC 2016 Title 24 Part 6 for outdoor use. Registration with CEC Appliance Database not required.
START TEMP	-30°C
FIELD SERVICEABLE LED	No
CONSTRUCTION	Aluminum
HARDWARE	Stainless Steel
FINISH	Marine Grade Powder Coat
LED LIFETIME	L70; 70,000 Hours
WARRANTY*	5 Years
WEIGHT	6.5 lbs.

* Visit techlighting.com for specific warranty limitations and details.



PORT 13 ROUND
shown in black



PORT 13 ROUND
shown in bronze




PORT 13 ROUND
shown in charcoal

ORDERING INFORMATION

700OWPRT	SHAPE	CRI / CCT	LENGTH	LENS	FINISH	VOLTAGE	DISTRIBUTION	OPTIONS
	R ROUND	930 90 CRI, 3000K	13 13"	F FROSTED	B BLACK Z BRONZE H CHARCOAL	UNV 120V-277V UNIVERSAL	S SYMMETRIC	NONE LF IN-LINE FUSE SP SURGE PROTECTION LFSP IN-LINE FUSE & SURGE PROTECTION

PORT 13 ROUND WALL




Port 13 Round

PHOTOMETRICS*

*For latest photometrics, please visit www.techlighting.com/OUTDOOR

PORT 13 ROUND

Total Lumen Output: 662
 Total Power: 32
 Luminaire Efficacy: 21
 Color Temp: 3000K
 CRI: 90
 BUG Rating: B0-U3-G1



PROJECT INFO

FIXTURE TYPE & QUANTITY

JOB NAME & INFO

NOTES



© 2017 Tech Lighting, L.L.C. All rights reserved. The "Tech Lighting" graphic is a registered trademark of Tech Lighting, L.L.C. Tech Lighting reserves the right to change specifications for product improvements without notification.



GENERATION BRANDS
 7400 Linder Avenue, Skokie, Illinois 60077

T 847.410.4400 F 847.410.4500